acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

SECTION 1: Identification

1.1 Product identifier

Trade name Cleansmart Gum Remover

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses solvent cleaner / degreaser

1.3 Details of the supplier of the safety data sheet

Cleansmart Technologies P. O. Box 2126 Loveland, Co. 80539 877-701-5271

Competent person responsible for the SDS Robert Blahnik

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency telephone number.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Annex | Hazard class and category | - Haz | ard statement code(s) | |
|-------|---|---------|-----------------------|------|
| B.6 | flammable liquid | Cat. 2 | (Flam. Liq. 2) | H225 |
| A.3 | serious eye damage/eye irritation | Cat. 2A | (Eye Irrit. 2A) | H319 |
| A.4S | skin sensitization | Cat. 1A | (Skin Sens. 1A) | H317 |
| A.5 | germ cell mutagenicity | Cat. 1B | (Muta. 1B) | H340 |
| A.6 | carcinogenicity | Cat. 1B | (Carc. 1B) | H350 |
| A.10 | aspiration hazard | Cat. 1 | (Asp. Tox. 1) | H304 |

Remarks

For full text of H-phrases: see SECTION 16.

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and chronic).

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Signal word dan |
|-----------------|
|-----------------|

Pictograms

GHS02, GHS07, GHS08







Hazard statements

| H225 | Highly flammable liquid and vapor. |
|------|---|
| H304 | May be fatal if swallowed and enters airways. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| | |

United States Page 1 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Precautionary statements

Precautionary statements - prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/eye protection/face protection.

Precautionary statements - response

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

IF ON SKIN: Wash with plenty of water.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

Precautionary statements - storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Precautionary statements - disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling

Naphtha (petroleum), hydrotreated light, orange oil, Distillates (petroleum), hydrotreated light

2.3 Other hazards

There is no additional information.

United States Page 2 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Hazard o | class and category | Hazard state- ment |
|---|----------------------|-----------|---|---|--|
| Naphtha (petroleum), hydrotreated light | CAS No 64742-49-0 | 50 - < 75 | B.6 A.5 A.6 A.10 | Flam. Liq. 2 Muta. 1B Carc. 1B Asp. Tox. 1 | H225 H340 H350 H304 |
| Distillates (petroleum), hydrotreated light | CAS No 64742-47-8 | 10 - < 25 | B.6 A.10 | Flam. Liq. 4 Asp. Tox. 1 | H227 H304 |
| Propan-2-ol | CAS No 67-63-0 | 5 - < 10 | B.6 A.3 A.8D | Flam. Liq. 2 Eye Irrit. 2A STOT SE 3 | H225 H319 H336 |
| ethylene glycol monobutyl ether | CAS No 111-76-2 | 1 - < 5 | B.6 A.1O A.1D A.11 A.2 A.3 | Flam. Liq. 4 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2A | H227 H302 H312 H332 H315 H319 |
| orange oil | CAS No 8028-48-6 | 1 - < 5 | B.6 A.2 A.4S A.10 | Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1A Asp. Tox. 1 | H226 H315 H317 H304 |

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

Provide fresh air.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

United States Page 3 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United States Page 4 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Incompatible substances or mixtures

Observe compatible storage of chemicals.

Consideration of other advice

Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to DOT) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

United States Page 5 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

| Coun- try | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Source |
|--------------|-------------------|----------|------------|--------------|----------------|---------------|-----------------|-------------|
| US | 2-butoxyethanol | 111-76-2 | PEL | 50 | 240 | | | 29 CFR OSHA |
| US | isopropyl alcohol | 67-63-0 | PEL | 400 | 980 | | | 29 CFR OSHA |

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless other-

vise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted av-

erage.

Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

United States Page 6 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid Color yellow

Odor characteristic

Other physical and chemical parameters

pH (value) not determined Melting point/freezing point not determined

Initial boiling point and boiling range 82.5 °C

Flash point 13 °C at 101.3 kPa 56 °F at 1 atm (closed cup)

Evaporation rate not determined
Flammability (solid, gas) not relevant (fluid)
Explosive limits not determined
Vapor pressure 4.3 kPa at 20 °C

Density 0.76 - 0.77 ^g/_{cm³} at 20 °C

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW) this information is not available

Auto-ignition temperature 230 °C

Viscosity not determined

Explosive properties none Oxidizing properties none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

· if heated

risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

United States Page 7 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Physical stresses which might result in a hazardous situation and have to be avoided strong shocks

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

| Name of substance | CAS No | Exposure route | ATE |
|---------------------------------|----------|-------------------|-------------------------------------|
| ethylene glycol monobutyl ether | 111-76-2 | oral | 1,746 ^{mg} / _{kg} |
| ethylene glycol monobutyl ether | 111-76-2 | dermal | 1,100 ^{mg} / _{kg} |
| ethylene glycol monobutyl ether | 111-76-2 | inhalation: vapor | 11 ^{mg} / _l /4h |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Summary of evaluation of the CMR properties

May cause genetic defects.

May cause cancer.

Shall not be classified as a reproductive toxicant.

Carcinogenicity

National Toxicology Program (United States):

none of the ingredients are listed

IARC Monographs

| Name of substance | Name acc. to inventory | CAS No | wt% | Classifica- tion | Remarks | Number |
|---------------------------------|------------------------|----------|-------|---------------------|---------|----------------------------|
| ethylene glycol monobutyl ether | 2-Butoxyethanol | 111-76-2 | 3.959 | 3 | | Volume 88 |
| Propan-2-ol | Isopropyl alcohol | 67-63-0 | 8.58 | 3 | | Volume 15, Sup 7, 71 |

Legend

3 Not classifiable as to carcinogenicity in humans.

United States Page 8 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture

| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
|------------------------------------|----------|----------|-------------------------------------|-----------------------|---------------|
| Propan-2-ol | 67-63-0 | LC50 | 10,000 ^{mg} / _l | fish | 96 h |
| ethylene glycol monobutyl ether | 111-76-2 | LC50 | 1,474 ^{mg} / _l | fish | 96 h |
| ethylene glycol monobutyl ether | 111-76-2 | EC50 | 1,550 ^{mg} / _l | aquatic invertebrates | 48 h |
| ethylene glycol monobutyl ether | 111-76-2 | ErC50 | 1,840 ^{mg} / _l | algae | 72 h |

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
|------------------------------------|----------|----------|--------------------------------------|-----------------------|---------------|
| Propan-2-ol | 67-63-0 | LC50 | >10,000 ^{mg} / _l | aquatic invertebrates | 24 h |
| ethylene glycol monobutyl ether | 111-76-2 | EC50 | 297 ^{mg} / _l | aquatic invertebrates | 21 d |

12.2 Persistence and degradability

Degradability of components of the mixture

| Name of substance | CAS No | Process | Degradation rate | Time |
|---------------------------------|-----------|---------------------------|------------------|------|
| Propan-2-ol | 67-63-0 | oxygen depletion | 53 % | 5 d |
| ethylene glycol monobutyl ether | 111-76-2 | carbon dioxide generation | 18.3 % | 3 d |
| orange oil | 8028-48-6 | oxygen depletion | 3 % | 28 d |
| orange oil | 8028-48-6 | DOC removal | 96 % | 28 d |

12.3 Bioaccumulative potential

Data are not available.

United States Page 9 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Bioaccumulative potential of components of the mixture

| Name of substance | CAS No | BCF | Log KOW | BOD5/COD |
|---------------------------------|-----------|-----|---------|----------|
| ethylene glycol monobutyl ether | 111-76-2 | | 0.81 | |
| orange oil | 8028-48-6 | | 5.6 | |

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number **1993**

14.2 UN proper shipping name Flammable liquid, n.o.s.

Technical name (hazardous constituents)Naphtha (petroleum), hydrotreated light, Propan-2-ol

14.3 Transport hazard class(es)

Class 3 (flammable liquids)

14.4 Packing group II (substance presenting medium danger)

14.5 Environmental hazards none (non-environmentally hazardous acc. to the dangerous goods regu-

lations)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

United States Page 10 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Information for each of the UN Model Regulations

• Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number 1993

Proper shipping name Flammable liquid, n.o.s.

Class 3
Packing group II
Danger label(s) 3



Special provisions (SP) IB2, T7, TP1, TP8, TP28

ERG No 128

• International Maritime Dangerous Goods Code (IMDG)

UN number 1993

Proper shipping name FLAMMABLE LIQUID, N.O.S.

Class 3
Packing group II
Danger label(s) 3



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-E

Stowage category B

• International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1993

Proper shipping name Flammable liquid, n.o.s.

Class 3
Packing group II
Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3, 274

E2

1 L

United States Page 11 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

SARA TITLE III (Superfund Amendment and Reauthorization Act)

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section none of the ingredients are listed 302 and 304)

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313)

| Name of substance | CAS No | Remarks | Effective date |
|-------------------|---------|---|----------------|
| Propan-2-ol | 67-63-0 | Only persons who manufacture by the strong acid process are subject, no supplier notifiction. | 1986-12-31 |

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

| Category | Rating | Description |
|-------------------------------|--------|---|
| Chronic | * | Chronic (long-term) health effects may result from repeated overexposure. |
| Health | 2 | Temporary or minor injury may occur. |
| Flammability | 3 | Material that can be ignited under almost all ambient temperature conditions. |
| Physical hazard | 0 | Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive. |
| Personal protective equipment | - | |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

| Category | Degree of hazard | Description |
|----------------|------------------|---|
| Flammability | 3 | Material that can be ignited under almost all ambient temperature conditions. |
| Health | 2 | Material that, under emergency conditions, can cause temporary incapacitation or residual injury. |
| Instability | 0 | Material that is normally stable, even under fire conditions. |
| Special hazard | | |

Right to Know Hazardous Substance List

| Name of substance | CAS No | Remarks | Classifications |
|---------------------------------|----------|---------|-----------------|
| ethylene glycol monobutyl ether | 111-76-2 | | CA F2 |
| Propan-2-ol | 67-63-0 | | F3 |

United States Page 12 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

Legend

CA Carcinogenic.

F2 Flammable - Second Degree. F3 Flammable - Third Degree.

Proposition 65 List of chemicals

none of the ingredients are listed

Relevant European Union (EU) safety, health and environmental provisions

Classification according to GHS (1272/2008/EC, CLP)

| Hazard class | Category | Hazard class and category |
|---|----------|---------------------------|
| flammable liquid | 2 | (Flam. Liq. 2) |
| serious eye damage/eye irritation | 2 | (Eye Irrit. 2) |
| skin sensitization | 1 | (Skin Sens. 1) |
| germ cell mutagenicity | 1B | (Muta. 1B) |
| carcinogenicity | 1B | (Carc. 1B) |
| aspiration hazard | 1 | (Asp. Tox. 1) |
| hazardous to the aquatic environment - chronic hazard | 3 | (Aquatic Chronic 3) |

SECTION 16: Other information, including date of preparation or last revision

16.2 Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|---------------|--|
| 29 CFR OSHA | 29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits) |
| 49 CFR US DOT | 49 CFR § 40 U.S. Department of Transportation |
| Acute Tox. | acute toxicity |
| Asp. Tox. | aspiration hazard |
| ATE | Acute Toxicity Estimate |
| BCF | BioConcentration Factor |
| BOD | Biochemical Oxygen Demand |
| Carc. | carcinogenicity |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| CLP | Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures |
| CMR | Carcinogenic, Mutagenic or toxic for Reproduction |
| COD | chemical oxygen demand |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DMEL | Derived Minimal Effect Level |
| DNEL | Derived No-Effect Level |
| DOT | Department of Transportation (USA) |
| EmS | Emergency Schedule |
| ERG No | Emergency Response Guidebook - Number |
| Eye Dam. | seriously damaging to the eye |
| Eye Irrit. | irritant to the eye |
| Flam. Liq. | flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |

United States Page 13 / 15

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

| Abbr. | Descriptions of used abbreviations |
|-----------------|---|
| HMIS | Hazardous Materials Identification System |
| IARC Monographs | IARC Monographs on the Evaluation of Carcinogenic Risks to Humans |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods Code |
| log KOW | n-octanol/water |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant) |
| Muta. | germ cell mutagenicity |
| NFPA® 704 | National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) |
| NPCA-HMIS® III | National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition |
| OSHA | Occupational Safety and Health Administration (United States) |
| PBT | Persistent, Bioaccumulative and Toxic |
| PEL | permissible exposure limit |
| PNEC | Predicted No-Effect Concentration |
| ppm | parts per million |
| Skin Corr. | corrosive to skin |
| Skin Irrit. | irritant to skin |
| Skin Sens. | skin sensitization |
| STEL | short-term exposure limit |
| STOT SE | specific target organ toxicity - single exposure |
| TWA | time-weighted average |
| vPvB | very Persistent and very Bioaccumulative |

16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200 49 CFR § 172.101 Hazardous Materials Table (DOT)

16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

16.5

List of relevant phrases (code and full text as stated in chapter 2 and 3)

| Code | Text |
|------|--|
| H225 | highly flammable liquid and vapor |
| H226 | flammable liquid and vapor |
| H227 | combustible liquid |
| H302 | harmful if swallowed |
| H304 | may be fatal if swallowed and enters airways |

United States Page 14 / 15

Safety Data Sheet acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Gum Remover

Version number: GHS 1.0 Date of compilation: 2016-07-19

| Code | Text |
|------|-------------------------------------|
| H312 | harmful in contact with skin |
| H315 | causes skin irritation |
| H317 | may cause an allergic skin reaction |
| H319 | causes serious eye irritation |
| H332 | harmful if inhaled |
| H336 | may cause drowsiness or dizziness |
| H340 | may cause genetic defects |
| H350 | may cause cancer |

16.7 **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States Page 15 / 15