

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

SECTION 1: Identification

1.1 Product identifier

Trade name **Cleansmart Rust Remover**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses **acidic cleaner**

1.3 Details of the supplier of the safety data sheet

Cleansmart Technologies
P. O. Box 2126
Loveland, Co. 80539
877-701-5271

Competent person responsible for the SDS **Robert Blahnik**

1.4 Emergency telephone number

Emergency information service **USA 1.800.535.5053, INTL 1.352.323.3500**
24 hour emergency telephone number.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Annex	-	Hazard class and category	-	Hazard statement code(s)	
A.2		skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
A.3		serious eye damage/eye irritation	Cat. 1	(Eye Dam. 1)	H318
A.4S		skin sensitization	Cat. 1A	(Skin Sens. 1A)	H317

Remarks

For full text of H-phrases: see SECTION 16.

Hazards not otherwise classified

Contains d-limonene. May produce an allergic reaction.

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word **danger**

Pictograms

GHS05, GHS07



Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary statements

Precautionary statements - prevention

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/eye protection/face protection.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Precautionary statements - response

IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Precautionary statements - disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling

d-limonene, ammonium bifluoride

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Hazard class and category		Hazard statement
ammonium bifluoride	CAS No 1341-49-7	1 - < 5	A.10 A.2 A.3	Acute Tox. 3 Skin Corr. 1B Eye Dam. 1	H301 H314 H318
polyethoxylated tallow amine	CAS No 61791-26-2	1 - < 5	A.10 A.1D	Acute Tox. 4 Acute Tox. 4	H302 H312
disodium cocoamphodipropionate	CAS No 68604-71-7	< 1	B.6	Flam. Liq. 4	H227
dipropylene glycol monomethyl ether	CAS No 34590-94-8	< 1	B.6	Flam. Liq. 4	H227
d-limonene	CAS No 5989-27-5	< 1	B.6 A.2 A.4S A.10	Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1A Asp. Tox. 1	H226 H315 H317 H304

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

SECTION 4: First-aid measures

4.1

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NO_x)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Handling of incompatible substances or mixtures

Keep away from

caustic solutions

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Incompatible substances or mixtures

Observe compatible storage of chemicals.

Control of the effects

Protect against external exposure, such as

frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
US	dipropylene glycol methyl ether	34590-94-8	PEL	100	600			29 CFR OSHA

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless to pale amber
Odor	sharp

Other physical and chemical parameters

pH (value)	2 - 4 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	not determined
Vapor pressure	31.69 hPa at 25 °C
Density	1.013 g/ml
Solubility(ies)	
Water solubility	miscible in any proportion

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Partition coefficient n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Physical stresses which might result in a hazardous situation and have to be avoided

strong shocks

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
ammonium bifluoride	1341-49-7	oral	130 mg/kg
polyethoxylated tallow amine	61791-26-2	oral	1,437 mg/kg
polyethoxylated tallow amine	61791-26-2	dermal	>1,260 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Carcinogenicity

- National Toxicology Program (United States): none of the ingredients are listed
- IARC Monographs none of the ingredients are listed

Name of substance	Name acc. to inventory	CAS No	wt%	Classification	Remarks	Number
d-limonene	d-Limonene	5989-27-5	0.49	3		Volume 73

Legend

3 Not classifiable as to carcinogenicity in humans.

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ammonium bifluoride	1341-49-7	LC50	421.4 mg/l	fish	96 h
polyethoxylated tallow amine	61791-26-2	LC50	0.19 mg/l	fish	96 h
polyethoxylated tallow amine	61791-26-2	LC50	0.99 mg/l	fish	96 h
polyethoxylated tallow amine	61791-26-2	EC50	0.008 mg/l	algae	48 h
polyethoxylated tallow amine	61791-26-2	EC50	0.47 mg/l	daphnia	48 h
dipropylene glycol mono-methyl ether	34590-94-8	LC50	>150 mg/l	fish	72 h
dipropylene glycol mono-methyl ether	34590-94-8	ErC50	>969 mg/l	algae	72 h
d-limonene	5989-27-5	LC50	720 µg/l	fish	96 h
d-limonene	5989-27-5	EC50	688 µg/l	fish	96 h

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
d-limonene	5989-27-5	EC50	0.85 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
dipropylene glycol mono-methyl ether	34590-94-8	oxygen depletion	75 %	10 d
dipropylene glycol mono-methyl ether	34590-94-8	DOC removal	96 %	28 d
dipropylene glycol mono-methyl ether	34590-94-8	carbon dioxide generation	76 %	28 d

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
dipropylene glycol mono-methyl ether	34590-94-8		0.0061	
d-limonene	5989-27-5		4.38	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

SECTION 14: Transport information

- 14.1** UN number (not subject to transport regulations)
- 14.2** UN proper shipping name not relevant
- 14.3** Transport hazard class(es)
Class -
- 14.4** Packing group not relevant
- 14.5** Environmental hazards none (non-environmentally hazardous acc. to the dangerous goods regulations)
- 14.6** Special precautions for user
There is no additional information.
- 14.7** Transport in bulk according to Annex II of MARPOL and the IBC Code
The cargo is not intended to be carried in bulk.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

SARA TITLE III (Superfund Amendment and Reauthorization Act)

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304) none of the ingredients are listed

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313) none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description
Chronic	/	None.
Health	3	Major injury likely unless prompt action is taken and medical treatment is given.
Flammability	0	Material that will not burn under typical fire conditions.
Physical hazard	0	Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive.
Personal protective equipment	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Category	Degree of hazard	Description
Flammability	1	Material that must be preheated before ignition can occur.
Health	3	Material that, under emergency conditions, can cause serious or permanent injury.
Instability	0	Material that is normally stable, even under fire conditions.
Special hazard		

Right to Know Hazardous Substance List

none of the ingredients are listed

Name of substance	CAS No	Remarks	Classifications
ammonium bifluoride	1341-49-7		CO
DPM	34590-94-8		F2

Legend

CO Corrosive.

F2 Flammable - Second Degree.

Proposition 65 List of chemicals

none of the ingredients are listed

Relevant European Union (EU) safety, health and environmental provisions

Classification according to GHS (1272/2008/EC, CLP)

Hazard class

skin corrosion/irritation

serious eye damage/eye irritation

hazardous to the aquatic environment - acute hazard

hazardous to the aquatic environment - chronic hazard

Category Hazard class and category

1B (Skin Corr. 1B)

1 (Eye Dam. 1)

1 (Aquatic Acute 1)

3 (Aquatic Chronic 3)

SECTION 16: Other information, including date of preparation or last revision

16.2 Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
Acute Tox.	acute toxicity
Asp. Tox.	aspiration hazard
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Abbr.	Descriptions of used abbreviations
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HMIS	Hazardous Materials Identification System
IARC Monographs	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	parts per million
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
Skin Sens.	skin sensitization
STEL	short-term exposure limit
TWA	time-weighted average
vPvB	very Persistent and very Bioaccumulative

16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

16.5

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	flammable liquid and vapor
H227	combustible liquid
H301	toxic if swallowed
H302	harmful if swallowed
H304	may be fatal if swallowed and enters airways
H312	harmful in contact with skin
H314	causes severe skin burns and eye damage
H315	causes skin irritation
H317	may cause an allergic skin reaction

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

Cleansmart Rust Remover

Version number: GHS 1.0

Date of compilation: 2016-07-19

Code	Text
H318	causes serious eye damage

16.7

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.